



IRRIGATION WATER SAVER
MAGNETIC GROWTH MASTER SERIES
WITH A SIZE FOR EVERY SITE FROM
5-1400 GPM / 3/4" TO 6" PIPES
MODELS MGM-750 TO MGM-6000

Unharness the powers of nature and science to improve plant penetration of even brackish water with less water needed. A low electric voltage is induced in the water by its flow through a strategically placed, strong (neodymium) magnetic field. The resulting energy imparted to the water causes it to cluster in stacked hexagonal planes while releasing a small percentage of hydrogen ions that create hydronium (H₃O). Such minor changes to water have been laboratory and field documented to cause water to travel further and more quickly in the xylem (capillary) system of plants. Even "bad" water.

- * NO ADDED CHEMICALS & NO ELECTRICITY & NO WASTED WATER
- * 10% PLUS WATER SAVINGS **PLUS** IMPROVED YIELDS
- * A SMALL FRACTION OF THE COST OF REVERSE OSMOSIS WITH ZERO MAINTENANCE

<u>MODEL</u>	<u>FLOW-GPM</u>	<u>PIPE SIZE-IN.</u>	<u>CONNECTION</u>	<u>WETTED MATERIALS</u>
MGM-750	10	3/4	Glued slip	PVC
MGM-1000	15	1	Glued slip	PVC
MGM-1500	100	1-1/2	Flange	SS & Bronze
MGM-2000	150	2	Flange	SS & Bronze
MGM-3000	340	3	Flange	SS & Bronze
MGM-4000	600	4	Flange	SS & Bronze
MGM-6000	1400	6	Flange	SS & Bronze

Units are bidirectional and may be installed vertically or horizontally
 A material and workmanship 15 year warranty accompanies each unit



Maximum temperature for magnet life is 100°F
 Maximum operating pressure is 100 PSI for MGM-750 , -1000 and 150 PSI for MGM-1500 through MGM-6000
 We will quote and construct custom sizes and materials upon request. Consult factory
 2575 Fortune Way Ste. J Vista, CA 92081
 760-734-5787 sales@dimewater.com